

Model	Q	Δp	P	I	~	U	p	L _{WA}	L _{PA}	t _{OPER}	Ø	D	m
	m³/h	Pa	W	A		V		dB(A)	dB(A)	°C	mm		kg
BDTX 100	240	300	60	0.30	1	230	2	51	44	40	100		2.6
BDTX 125	315	300	80	0.40	1	230	2	50	43	40	125		2.7
BDTX 150	422	315	78	0.40	1	230	2	53	46	40	150		3
BDTX 160	440	310	85	0.40	1	230	2	52	45	40	160		3.2
BDTX 200 A	735	400	90	0.43	1	230	2	53	46	40	200		4.4
BDTX 200 B	875	450	100	0.51	1	230	2	54	48	40	250		4.8
BDTX 250 A	1010	500	140	0.69	1	230	2	52	45	40	250		4.9
BDTX 250 B	1150	550	145	0.74	1	230	2	54	47	40	250		5.3
BDTX 315 A	1450	660	160	0.80	1	230	2	54	48	40	315		6.8
BDTX 315 B	1750	660	180	0.87	1	230	2	56	49	40	315		6.9
BDTX 355 A	1300	255	135	1.00	1	230	2	52	45	40	355		9
BDTX 355 B	2620	870	450	1.94	1	230	2	60	54	40	355		10