

Model	Q m³/h	Δp Pa	P W	I A	~	U V	p	L _{WA} dB(A)	L _{PA} dB(A)	t _{OPER} °C	Ø D mm	m kg
BSM 250-2K	2200	240	150	1.00	1	230	2	82	61	40	250	7.4
BSM 250	1200	36	125	0.60	1	230	4	66	45	40	250	7.4
BSM 300	2000	60	165	0.79	1	230	4	69	48	40	300	8
BSM 350	3250	75	210	0.92	1	230	4	74	53	40	350	8.2
BSM 400	4500	90	220	0.97	1	230	4	77	56	40	400	8.8
BSM 450	5000	100	300	1.32	1	230	4	81	60	40	450	10
BSM 500	5500	90	320	1.40	1	230	4	83	62	40	500	11
BSM 550	6000	60	375	1.65	1	230	4	85	63	40	550	14.6
BSM 600	8000	50	390	1.71	1	230	4	86	65	40	600	15.6
BST 250-2K	2200	240	190	1.00	3	400	2	82	61	40	250	7.4
BST 250	1200	36	95	0.35	3	400	4	66	45	40	250	7.4
BST 300	2000	60	145	0.40	3	400	4	69	48	40	300	8
BST 350	3250	75	230	0.44	3	400	4	74	53	40	350	8.2
BST 400	4500	90	250	0.47	3	400	4	77	56	40	400	0
BST 450	5000	100	270	0.55	3	400	4	81	60	40	450	10
BST 500	5500	90	340	0.60	3	400	4	83	62	40	500	11
BST 550	6000	90	385	0.70	3	400	4	85	63	40	550	14.6
BST 600	8000	80	395	0.72	3	400	4	86	65	40	600	15.6